

Social Network Interdiction: Reducing the Capabilities of a Terrorist Network

Yazid Sufaat

Two Original Al Qaeda Suspects

halid Almihdhar

Convright © 2001, Valdis Krebs

Salem Alhazmi

Majed Moged

Nawaf Alhazmi

Mohamed Abdi

Mahamed Atta

Abdul Aziz Alomar

Ahmed Alghamdi

Hamza Alghamdi

Saeed Alghamd

Cole Bombing Suspects

Walid Ba' Attash [Khallad]

Fahad al Quso

Ahmed Al-Hada

Flight AA #11 - Crashed into WTC North

■ Flight UA #93 - Crashed in Pennsylvania ■ Flight UA #175 - Crashed into WTC Sout ■ Other Associates of Hijackers

By: Allison Aichele
MIDN 1/C
United States Naval Academy

maintaining the data needed, and c including suggestions for reducing	lection of information is estimated to ompleting and reviewing the collect this burden, to Washington Headqu uld be aware that notwithstanding an DMB control number.	ion of information. Send comments arters Services, Directorate for Infor	regarding this burden estimate of mation Operations and Reports	or any other aspect of the 1215 Jefferson Davis	nis collection of information, Highway, Suite 1204, Arlington		
1. REPORT DATE APR 2010		2. REPORT TYPE		3. DATES COVERED 00-00-2010 to 00-00-2010			
4. TITLE AND SUBTITLE				5a. CONTRACT	NUMBER		
Social Network Int Network	erdiction:Reducing	a Terrorist	5b. GRANT NUMBER				
Network			5c. PROGRAM ELEMENT NUMBER				
6. AUTHOR(S)			5d. PROJECT NUMBER				
			5e. TASK NUMBER				
			5f. WORK UNIT NUMBER				
	ZATION NAME(S) AND AD),21402	8. PERFORMING ORGANIZATION REPORT NUMBER				
9. SPONSORING/MONITO		10. SPONSOR/MONITOR'S ACRONYM(S)					
				11. SPONSOR/M NUMBER(S)	ONITOR'S REPORT		
12. DISTRIBUTION/AVAII Approved for publ	LABILITY STATEMENT ic release; distributi	on unlimited					
	otes fessional Developmo 15 April 2010, Army	-	-	,	Solution		
14. ABSTRACT							
15. SUBJECT TERMS							
16. SECURITY CLASSIFIC	17. LIMITATION OF	18. NUMBER	19a. NAME OF				
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified	Same as Report (SAR)	OF PAGES 16	RESPONSIBLE PERSON		

Report Documentation Page

Form Approved OMB No. 0704-0188




Introduction

- Who: 1/C Midshipman Honors Applied Mathematics Major at the United States Naval Academy. After graduation I will be in the U.S. Marine Corps.
- What: This project is my Senior Honors' project.
- Why: The events of 9/11 had a profound effect on me.



Sample Network



Maximum Flow Model

$$\max_{x \in A} x_{ts}$$
subject to:
$$\sum_{(i,j) \in FS(i)} x_{ij} - \sum_{(i,j) \in RS(i)} x_{ji} = \begin{cases} x_{ts} & \text{for } i = s \\ 0 & \text{for all } i \in N \setminus \{s,t\} \\ -x_{ts} & \text{for } i = t \end{cases}$$

$$0 \le x_{ij} \le u_{ij}$$

$$\forall (i,j) \in A$$

Where the x's represent the flow along any arc in a network and the u's represent the upper bound of the flow on an arc. The arc x(t,s) is an artificial arc that represents the maximum flow through the network



Node Interdiction

- Terrorists want to maximize the flow of information from the planners to the people conducting the terrorist act.
- I want to minimize the flow of information.
- Arc interdiction is challenging due to current communications technology.
- Node interdiction (terrorist capture) is our solution.



Node Interdiction Model Minimize the Maximum Flow



Inner Dual of Node Interdiction Model

$$\begin{array}{ll} \min_{w \in N} & \min_{\theta, \pi, \gamma} & \sum_{(i, j) \in A} \mu_{ij} \left(1 - w_i \right) \gamma_{ij} + \sum_{(i, j) \in A} \mu_{ij} \left(1 - w_j \right) \gamma_{ji} \\ & \text{subject to:} & \theta_i - \theta_j + \pi_{ij} + \gamma_{ij} + \gamma_{ji} & \geq 0 \\ & \theta_t - \theta_s & = 1 \\ & \sum_{i \in N} r_i w_i & \leq R \\ & \pi_{ij} \geq 0 & \forall (i, j) \in A \\ & \gamma_{ij} \geq 0 & \forall (i, j) \in A \\ & w_i \in \left\{ 0, 1 \right\} & \forall i \in N \end{array}$$

The dual of the inner problem causes the objective function to become non-linear.



Linearization of the objective function for the Node Interdiction Model

$$\min_{w \in N} \quad \min_{\theta, \pi, \gamma}$$

 $\sum_{(i,j)\in A} \mu_{ij}\beta_{ij} + \sum_{(i,j)\in A} \mu_{ij}\beta_{ij}$

subject to: $\theta_i - \theta_j + \pi_{ij} + \gamma_{ij} + \gamma_{ii} \ge 0 \ \forall (i, j) \in A, \forall i \in N$

 $\theta_t - \theta_s$

Technique described by Wood (1993) for

Arc interdiction

 $\beta_{ij} - \gamma_{ij} + w_i$

 $\geq 0 \ \forall (i,j) \in A, \forall i \in N$

 $\beta_{ii} - \gamma_{ii} + w_i$

 $\geq 0 \ \forall (i,j) \in A, \forall i \in N$

 $\sum_{i \in N} r_i w_i$

 $\leq R$

 $\pi_{ii} \ge 0$

 $\forall (i,j) \in A$

 $\gamma_{ij} \ge 0$

 $\forall (i,j) \in A$


 $w_i \in \{0,1\}$

 $\forall (i,j) \in A$

 $\beta_{ii} \in \{0,1\}$

 $\forall (i,j) \in A$











Krebs' Model



Krebs' 9/11 Network Depiction- 1 degree from the 9/11 original suspects





Results and recommendations

- For a given level of resources and the knowledge of the cost to search/capture a terrorist the model identifies which terrorist(s) should be pursued.
- Follow-on: Examine a model to determine the minimum cost to eliminate the terrorist network activity.


Extra Slides

Results of Model

	R										
Terrorist	1000	2000	3000	4000	5000	6000	7000	8000	9000	10000	
1	0	0	0	0	0	0	0	0	0	1	
2	0	0	0	0	0	0	0	0	0	0	
3	0	0	0	0	1	0	0	0	0	0	
4	0	0	0	0	0	1	0	0	0	0	
5	0	0	0	0	0	0	0	0	0	0	
6	0	0	0	0	0	0	0	0	0	0	
7	0	0	0	0	0	0	0	0	0	0	
8	0	1	0	0	0	0	1	1	1	0	
9	0	0	1	1	0	0	1	1	1	0	
10	0	0	0	1	0	0	0	1	1	0	
11	1	1	1	0	0	1	1	0	1	0	
12	0	0	1	0	0	0	1	1	1	0	
13	0	0	0	1	0	0	1	1	1	0	
14	0	0	0	0	0	0	1	1	1	0	
15	0	0	0	0	0	0	1	1	1	0	
cost	500	2000	3000	4000	5000	5500	7000	8000	8500	10000	

Minimum Cut Model

$$\begin{aligned} & \min_{\theta,\pi} \quad 3\pi_{s1} + 4\pi_{s2} + 4\pi_{13} + 2\pi_{23} + 3\pi_{24} + 3\pi_{3t} + 4\pi_{4t} \\ & \theta_s - \theta_1 + \pi_{s1} \geq 0 \\ & \theta_s - \theta_2 + \pi_{s2} \geq 0 \\ & \theta_1 - \theta_3 + \pi_{13} \geq 0 \\ & \theta_2 - \theta_3 + \pi_{23} \geq 0 \\ & \theta_2 - \theta_4 + \pi_{24} \geq 0 \\ & \theta_3 - \theta_t + \pi_{3t} \geq 0 \\ & \theta_4 - \theta_t + \pi_{4t} \geq 0 \\ & \theta_t - \theta_s = 1 \\ & \pi_{ij} \geq 0 \ \forall \ (i,j) \in A \\ & \theta_i \text{ is unrestricted in sign} \end{aligned}$$



1

Nodes of the Network

- where 1. Mohamed Atta
- Ramzi Bin al-Shibh
- 3. Hani Hanjour
- 4. Nawaf Alhazmi
- 5. Abdul Aziz Alomari
- 6. Khalid Almihdhar
- 7. Ahmed Alghamdi
- 8. Salem Alhazmi
- 9. Majed Moqed
- 10. Yazid Sufaat
- 11. Ahmed Al-Hada
- 12. Hamza Alghamdi
- 13. Saeed Alghamdi
- 14. Ahmed Alnami
- 15. Mohamed Abdi